## **Kel-Crete Industries, Inc.**

General Partner of CJG LP

PO Box 52217 Tulsa, OK 74152-0217 Phone: 918-744-0800, 800-845-1833

Fax: 918-744-0885

E-Mail: kelcrete@sbcglobal.net WWW: Kel-Crete.com

## **Suggested Mix Design for Masonry Mortar**

Kel-Crete is a non-toxic, non-hazardous admixture that performs as a **water reducer, plasticizer, air-entraining agent and gelling** for your masonry mortar. For you to obtain all of the cost saving benefits please follow the start-up directions below.

## Start-up directions (1 sack mix):

- 1. Add 4 to 5 gallons of water to the mixer.
- 2. Add 3 ounces of Kel-Crete admixture to the water.
- 3. Add 50% of the masonry sand to the mixer.
- 4. Add a 94-pound sack of Portland Type I-II common cement to the mixer.
- 5. Add the balance of the masonry sand to the mixer.
- 6. Mix the total mix for 3 to 5 minutes.
- 7. **If needed** add small amounts of water to reach your desired consistency.

## **Notes:**

- a. Do not mix over 10 minutes.
- b. To obtain longer board life break the set by stopping the mix for 2 minutes, and then mix again for 2 minutes.
- c. This mix design will give you 35% to 40% more volume of the mortar than the pre-blended bagged products can.
- d. This total mix will save you huge material, labor, fuel costs, etc.

Call 800-845-1833 for service.